



# 中国国家强制性产品认证证书

证书编号: 2024010305681650

认证委托人名称及地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

生产者名称及地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

生产企业名称及地址

建兴电机株式会社

(Jang-an-dong) 183, Hancheon-ro, Dongdaemun-gu, Seoul, Korea

产品名称和系列、型号、规格

按钮开关

KBL30,KSL30,KPB30,KH-30(型号解释详见附页); Uimp:1.5kV;

Ui=AC500V;Ith=10A;Ue=AC250V,Ie=6A;Ue=AC125V, Ie=10A; AC-15;φ30;IP65(W型),IP40(无 W 型)

产品标准和技术要求

GB/T 14048.5-2017

上述产品符合《强制性产品认证实施规则 低压电器 低压元器件》  
(CNCA-C03-02:2024) 的要求, 特发此证。

发证日期: 2024 年 09 月 02 日 有效期至: 2029 年 09 月 01 日

证书信息和有效性可扫描下方二维码或登录发证机构网站查验,  
也可在认监委网站 ([www.cnca.gov.cn](http://www.cnca.gov.cn)) 查询。



签发:

谢肇煦



中国质量认证中心  
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司







# 中国国家强制性产品认证证书

证书编号: 2024010305681650

证书附页: 第 1 页 共 2 页

## KPB □□□-□□□ 控制按钮开关

①②③ ④⑤⑥

① Mounting hole 30: Φ30

② -: IP40 | W: IP65

③ M: momentary pushbutton switch | MS: 2 step selectable pushbutton switch(1 step: push function/2 step: push function) | ML: 2 step selectable pushbutton switch(1 step: push function/2 step: push non- function) | AT: alternate pushbutton switch | EM: mushroom headed momentary pushbutton switch | EA: mushroom headed alternate pushbutton switch | ER: push lock & turn reset pushbutton switch | EP: push lock & pull reset pushbutton switch

④ R: red | G: green | Y: yellow | O: orange | W: white | B: blue

⑤ number of NO contacts

⑥ number of NC contacts

注: ④、⑤、⑥项内容可不在铭牌上标识, 仅在包装箱上标识。

## KBL □□□-□□□□□ 指示按钮开关

①②③ ④⑤⑥⑦⑧

① Mounting hole 30: Φ30

② -: IP40 | W: IP65

③ M: momentary pushbutton switch | MP: momentary pushbutton switch with protective ring | MS: 2 step selectable pushbutton switch(1 step: push function/2 step: push function) | ML: 2 step selectable pushbutton switch(1 step: push function/2 step: push non- function) | AT: alternate pushbutton switch | EM: mushroom headed momentary pushbutton switch | EA: mushroom headed alternate pushbutton switch | ER: push lock & turn reset pushbutton switch | EP: push lock & pull reset pushbutton switch

④ -: filament lamp | L: LED lamp

⑤ input voltage 1A: AC 110V 50/60Hz | 2A: AC 220V 50/60Hz | 3A: AC 230V 50/60Hz | 1C: 6V(LED lamp) or 6.3V(filament lamp) AC/DC | 2C: 12V AC/DC | 3C: 24V AC/DC

⑥ R: red | G: green | Y: yellow | W: white | B: blue

⑦ number of NO contacts

⑧ number of NC contacts

注: ⑥、⑦、⑧项内容可不在铭牌上标识, 仅在包装箱上标识。

## KSL □□□-□□□ 选择按钮开关

①②③ ④⑤

① Mounting hole 30: Φ30

本页为证书附页, 应与证书主页同时使用。



中国质量认证中心  
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司





# 中国国家强制性产品认证证书

证书编号：2024010305681650

证书附页：第 2 页 共 2 页

② -: IP40 | W: IP65

③ S2: 2 step manual return short lever | S3: 3 step manual return short lever | L2: 2 step manual return long lever | L3: 3 step manual return long lever | AS2: 2 step auto-return short lever | AS3: 3 step auto-return short lever | RS3: 3 step left-manual, right-auto-return short lever | AL2: 2 step auto-return long lever | AL3: 3 step auto-return long lever | RL3: 3 step left-manual, right-auto-return long lever | K2: 2 step manual-return key switch | K3: 3 step manual-return key switch | AK2: 2 step auto-return key switch | AK3: 3 step auto-return key switch | RK3: 3 step left-manual, right-auto-return key switch

④ number of NO contacts

⑤ number of NC contacts

注：④、⑤项内容可不在铭牌上标识，仅在包装箱上标识。

**KH-□□□□-□□ 控制按钮开关 Momentary pushbutton switch**

①②③④ ⑤⑥

① Mounting hole 30: Φ30

② -: IP40

③ 08 : case material : Nylon Glassl;

81 : case material : phenol;

46 : case material : ZnDc;

40 : case material : phenol, button guide:Φ48

65 : case material : ZnDc, button guide:Φ75

66 : case material : ZnDc, button guide:Φ75

④ EB: mushroom headed; ER: push lock & turn reset;

⑤ number of NO contacts

⑥ number of NC contacts

注：(1)⑤、⑥项内容可不在铭牌上标识，仅在包装箱上标识。

(2)①②③④组合的型号有：KH-3008, KH-3081, KH-3081EB, KH-3040, KH-3046ER, KH-3065EB, KH-3066EB。

本页为证书附页，应与证书主页同时使用。



**中国质量认证中心**

CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司





# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，  
不得单独使用  
This translated document  
does not have legal validity and  
cannot be used in isolation

**CERTIFICATE NO.:** 2024010305681650

**NAME AND ADDRESS OF THE APPLICANT**

KUN HUNG ELECTRIC CO.,LTD.

(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

**NAME AND ADDRESS OF THE MANUFACTURER**

KUN HUNG ELECTRIC CO.,LTD.

(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

**NAME AND LOCATION OF THE FACTORY**

KUN HUNG ELECTRIC CO.,LTD.

(Jang-an-dong)183,Hancheon-ro,Dongdaemun-gu, Seoul, Korea

**PRODUCT NAME,MODEL AND SPECIFICATION**

Push-button Switch

KBL30,KSL30,KPB30,KH-30; Uimp:1.5kV ; Ui=AC500V;Ith=10A;Ue=AC250V,Ie=6A;Ue=AC125V,  
Ie=10A; AC-15;φ30;IP65(W),IP40(non-W)

**STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS**

GB/T 14048.5-2017

This is to certify that the above mentioned product(s) complies with the requirements of  
implementation rules for compulsory certification(REFNO. CNCA-C03-02:2024).

**Valid from:** Sep.02,2024

**Valid until:** Sep.01,2029

The certificate information and validity could be checked by scanning the QR code below or logging in to  
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).



**SIGNATURE:**

谢肇煦



**中国质量认证中心**  
CHINA QUALITY CERTIFICATION CENTRE

**CHINA QUALITY CERTIFICATION CENTRE CO., LTD.**





# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2024010305681650

Appendix: Page 1 of 2

本翻译文件不具有法律效力，  
不得单独使用  
This translated document  
does not have legal validity and  
cannot be used in isolation

## KPB □□□-□□□ 控制按钮开关

①②③ ④⑤⑥

① Mounting hole 30:  $\Phi 30$

② -: IP40 | W: IP65

③ M: momentary pushbutton switch | MS: 2 step selectable pushbutton switch(1 step: push function/2 step: push function) | ML: 2 step selectable pushbutton switch(1 step: push function/2 step: push non- function) | AT: alternate pushbutton switch | EM: mushroom headed momentary pushbutton switch | EA: mushroom headed alternate pushbutton switch | ER: push lock & turn reset pushbutton switch | EP: push lock & pull reset pushbutton switch

④ R: red | G: green | Y: yellow | O: orange | W: white | B: blue

⑤ number of NO contacts

⑥ number of NC contacts

注: ④、⑤、⑥项内容可不在铭牌上标识，仅在包装箱上标识。

## KBL □□□-□□□□□ 指示按钮开关

①②③ ④⑤⑥⑦⑧

① Mounting hole 30:  $\Phi 30$

② -: IP40 | W: IP65

③ M: momentary pushbutton switch | MP: momentary pushbutton switch with protective ring | MS: 2 step selectable pushbutton switch(1 step: push function/2 step: push function) | ML: 2 step selectable pushbutton switch(1 step: push function/2 step: push non- function) | AT: alternate pushbutton switch | EM: mushroom headed momentary pushbutton switch | EA: mushroom headed alternate pushbutton switch | ER: push lock & turn reset pushbutton switch | EP: push lock & pull reset pushbutton switch

④ -: filament lamp | L: LED lamp

⑤ input voltage 1A: AC 110V 50/60Hz | 2A: AC 220V 50/60Hz | 3A: AC 230V 50/60Hz | 1C: 6V(LED lamp) or 6.3V(filament lamp) AC/DC | 2C: 12V AC/DC | 3C: 24V AC/DC

⑥ R: red | G: green | Y: yellow | W: white | B: blue

⑦ number of NO contacts

⑧ number of NC contacts

注: ⑥、⑦、⑧项内容可不在铭牌上标识，仅在包装箱上标识。

## KSL □□□-□□ 选择按钮开关

①②③ ④⑤

① Mounting hole 30:  $\Phi 30$

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心  
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，  
不得单独使用  
This translated document  
does not have legal validity and  
cannot be used in isolation

CERTIFICATE NO. : 2024010305681650

Appendix: Page 2 of 2

- ② -: IP40 | W: IP65  
③ S2: 2 step manual return short lever | S3: 3 step manual return short lever | L2: 2 step manual return long lever | L3: 3 step manual return long lever | AS2: 2 step auto-return short lever | AS3: 3 step auto-return short lever | RS3: 3 step left-manual, right-auto-return short lever | AL2: 2 step auto-return long lever | AL3: 3 step auto-return long lever | RL3: 3 step left-manual, right-auto-return long lever | K2: 2 step manual-return key switch | K3: 3 step manual-return key switch | AK2: 2 step auto-return key switch | AK3: 3 step auto-return key switch | RK3: 3 step left-manual, right-auto-return key switch

④ number of NO contacts

⑤ number of NC contacts

注：④、⑤项内容可不在铭牌上标识，仅在包装箱上标识。

**KH-□□□□-□□ 控制按钮开关 Momentary pushbutton switch**

①②③④ ⑤⑥

① Mounting hole 30: Φ30

② -: IP40

③ 08 : case material : Nylon Glassl;

81 : case material : phenol;

46 : case material : ZnDc;

40 : case material : phenol, button guide:Φ48

65 : case material : ZnDc, button guide:Φ75

66 : case material : ZnDc, button guide:Φ75

④ EB: mushroom headed; ER: push lock & turn reset;

⑤ number of NO contacts

⑥ number of NC contacts

注：(1)⑤、⑥项内容可不在铭牌上标识，仅在包装箱上标识。

(2)①②③④组合的型号有：KH-3008, KH-3081, KH-3081EB, KH-3040, KH-3046ER, KH-3065EB, KH-3066EB。

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心  
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.